

## Jan/2019 Valid 400-351 PDF and VCE Free Download in Braindump2go[Q201-Q211

**January/2019 Braindump2go 400-351 Exam Dumps with PDF and VCE New Updated Today! Following are some new 400-351 Real Exam Questions:**1.]2019 Latest 400-351 Exam Dumps (PDF & VCE) 502Q&As Download:

**https://www.braindump2go.com/400-351.html2.]2019 Latest 400-351 Exam Questions & Answers Download:**

**https://drive.google.com/drive/folders/0B75b5xYLjSSNa0JFbF9Gd3ZBU1E?usp=sharing**QUESTION 201 Which three statements about the high availability configuration on the Cisco 5760 WLCs are true? (Choose three.)  
A. Cisco WLC with more reboots is elected as active when the default stack priority is in use.  
B. EtherChannel bundles all ports on both active and standby Cisco WLC on a logical port.  
C. Cisco 5760 WLC uses a dedicated high availability port for high availability and configuration synchronization.  
D. High availability switchover is triggered when one of the ports on the active Cisco WLC EtherChannel bundle fails.  
E. Active Cisco WLCs in a pair can be identified using LED state without issuing any command on the Cisco WLC console.  
F. Cisco WLC with the highest priority in a stack are elected as the active Cisco WLC during the election process.  
G. All configuration including certificates are automatically synced between active and standby Cisco WLC.  
**Answer: BEF**QUESTION 202 Which statement about network automation and/or network orchestration is true?  
A. Automation focuses on coordinating multiple tasks at the same time.  
B. Orchestration and automation focus on a single task at a time.  
C. Orchestration focuses on coordinating multiple tasks at the same time.  
D. Automation and orchestration focus on coordinating multiple tasks at the same time.  
**Answer: C**QUESTION 203 When your wireless client device roams from one AP to another on the same network, which IEEE protocol can be used to authenticate the clients faster?  
A. 802.11r also called Assisted Roaming  
B. 802.11k also called Assisted Roaming  
C. 802.11r also called Fast BSS Transition  
D. 802.11k also called Predictive Based Roaming  
E. 802.11r also called Predictive Based Roaming  
F. 802.11k also called Fast BSS Transition  
**Answer: C**QUESTION 204 VLAN Trunking Protocol is a Cisco proprietary protocol that propagates the definition of VLANs over the local area network. Which two statements are true? (Choose two.)  
A. VTP requires access mode interfaces to propagate.  
B. VTP requires trunk mode interfaces to propagate.  
C. VTP transparent mode forwards VTP packets and can act as a client or a server.  
D. VTP config revision increases base on switch uptime.  
E. When Cisco switches are started from scratch, they are in server mode and their domain is set to null.  
**Answer: BE**QUESTION 205 You have configured VideoStream on a Cisco WLC and users are now viewing the company video broadcast over the wireless network. How can you verify you have VideoStream configured and working in the Cisco WLC GUI?  
A. The Multicast Status shows "Normal Multicast" in the Multicast Group Details.  
B. The Multicast Status shows "MediaStream Ongoing" in the Client detail page.  
C. The Multicast Status shows "Multicast-direct Allowed" in the Multicast Group Details.  
D. The Multicast Status shows "MediaStream Allowed" in the Multicast Group Details.  
**Answer: C**QUESTION 206 Drag and Drop Question Drag and drop the events involved in a typical location tracking workflow from the left into the correct order on the right. Not all items are used. **Answer:** QUESTION 207 You are the network administrator of a Cisco Autonomous AP deployment. You want to stop a client with MAC address 5057.a89e.b1f7 and IP address 10.0.0.2 from associating to your APs. Which configuration do you use? **Answer:** DQUESTION 208 You are the wireless administrator for ACME corporation. You must configure a Cisco Catalyst 3850 Series Switch to work as mobility agent to allow access point association to this switch. Which statement about this scenario is true?  
A. Access points must be connected to an access port that has the access VLAN configured to be the same as the service port VLAN on the Catalyst 3850 switch.  
B. Access points must be connected to a trunk port with the native VLAN set to 1 in order to join the WLC on the Catalyst 3850 switch.  
C. Access points must be connected to an access port with the access VLAN configured to the same as the wireless management VLAN on the Catalyst 3850 switch.  
D. Access points must be connected to an access port that has the access VLAN configured to be the same as the management VLAN for the switch stack.  
E. Access points must be connected to an access port with the access VLAN configured to be any VLAN that has a Layer 3 interface (SVI) on the Catalyst 3850 switch.  
**Answer: C**QUESTION 209 Which major block is not included in the ETSI Network Function Virtualization reference framework?  
A. Network Function Virtualization Infrastructure.  
B. Network Function Virtualization Management and Orchestration.  
C. Network Function Virtualization Policy Manager.  
D. Virtualized Network Function/ Element Management Systems.  
**Answer: C**QUESTION 210 With the introduction of mDNS policies in AireOS release 8.0, the administrator can configure to identify who uses the Bonjour service instances and in which location. Based on user 802.1x authentication, a AAA server/ISE can be configured to return which two possible values in the form of a "CISCO-AV-PAIR"? (Choose two.)  
A. Client-role  
B. User-role  
C. User-IDD.  
D. Bonjour-profile  
E. Client-location  
**Answer: BD**QUESTION 211 Which statement about the integration of ISE with Cisco Prime Infrastructure version 2.2 is true?  
A. Cisco Prime Infrastructure can display ISE profiling attributes for authenticated and unauthenticated clients.  
B. Cisco Prime Infrastructure can collect client authentication details from upto three

configured ISE servers.C. ISE can be added to Cisco Prime Infrastructure only using user credentials of admin user configured locally on ISE.D. When two instances of ISE are added to Cisco Prime Infrastructure. One must be working in secondary mode.

**Answer: D!!!RECOMMEND!!!1.**|2019 Latest 400-351 Exam Dumps (PDF & VCE) 502Q&As Download:

**<https://www.braindump2go.com/400-351.html>**2.|**2019 Latest 400-351 Study Guide Video:** YouTube Video:

[YouTube.com/watch?v=hZZnd7gWQik](https://www.youtube.com/watch?v=hZZnd7gWQik)